

Package: EconCausal (via r-universe)

June 2, 2026

Type Package

Title Causal Analysis for Macroeconomic Time Series (ECM-MARS, BSTS, Bayesian GLM-AR(1))

Version 1.0.2

Description Implements three complementary pipelines for causal analysis on macroeconomic time series: (1) Error-Correction Models with Multivariate Adaptive Regression Splines (ECM-MARS), (2) Bayesian Structural Time Series (BSTS), and (3) Bayesian GLM with AR(1) errors validated with Leave-Future-Out (LFO). Heavy backends (Stan) are optional and never used in examples or tests.

VignetteBuilder knitr

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.1)

Imports brms, readxl, dplyr, tidyr, tibble, purrr, bsts, BoomSpikeSlab, tseries, urca, vars, progressr, future.apply, rlang, magrittr, parallel, stats, utils

Suggests knitr, cmdstanr, rstan, future, RhpcBLASctl, rmarkdown, testthat (>= 3.0.0)

URL <https://github.com/IsadoreNabi/EconCausal>

BugReports <https://github.com/IsadoreNabi/EconCausal/issues>

Additional_repositories <https://stan-dev.r-universe.dev>

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/testthat/edition 3

Language en-US

NeedsCompilation no

Author José Mauricio Gómez Julián [aut, cre]

Maintainer José Mauricio Gómez Julián <isadore.nabi@pm.me>

Config/pak/sysreqs make libicu-dev libssl-dev

Repository <https://isadorenabi.r-universe.dev>

Date/Publication 2025-10-24 03:14:37 UTC

RemoteUrl <https://github.com/IsadoreNabi/EconCausal>

RemoteRef HEAD

RemoteSha a83710eb861e1a3205bf28f46201ff6dddea3d34

Contents

bglmar1	2
bsts_model	4
ecm_mars	6
Index	9

bglmar1

Bayesian Generalized Linear Model with AR(1) Errors

Description

Implements a Bayesian GLM with autoregressive errors of order 1 for causal inference between economic variables, with emphasis on temporal stability through Leave-Future-Out cross-validation.

Usage

```
bglmar1(
  data_path,
  circ_vars,
  prod_vars,
  max_lag = 3,
  initial_frac = 0.7,
  initial_min = 90,
  test_h = 12,
  step_h = 12,
  lfo_window = "sliding",
  chains = 4,
  parallel_chains = 4,
  iter = 1500,
  warmup = 750,
  adapt_delta = 0.95,
  trees = 12,
  seed = 2025,
  support_min = 0.6,
  folds_min = 5,
```

```

    sup_hi = 0.7,
    sup_lo = 0.6,
    backend = c("auto", "rstan", "cmdstanr")
  )

```

Arguments

<code>data_path</code>	Path to Excel file containing the data
<code>circ_vars</code>	Character vector of circulation variable names
<code>prod_vars</code>	Character vector of production variable names
<code>max_lag</code>	Maximum number of lags for independent variables (default: 3)
<code>initial_frac</code>	Initial fraction of data for training (default: 0.7)
<code>initial_min</code>	Minimum number of observations for initial training (default: 90)
<code>test_h</code>	Test horizon in months (default: 12)
<code>step_h</code>	Step size between folds in months (default: 12)
<code>lfo_window</code>	Type of window for LFO ("sliding" or "expanding", default: "sliding")
<code>chains</code>	Number of MCMC chains (default: 4)
<code>parallel_chains</code>	Number of parallel chains (default: 4)
<code>iter</code>	Total iterations per chain (default: 1500)
<code>warmup</code>	Warmup iterations per chain (default: 750)
<code>adapt_delta</code>	Adapt delta parameter for NUTS (default: 0.95)
<code>trees</code>	Maximum tree depth for NUTS (default: 12)
<code>seed</code>	Random seed (default: 2025)
<code>support_min</code>	Minimum support threshold for stable relationships (default: 0.6)
<code>folds_min</code>	Minimum number of folds required (default: 5)
<code>sup_hi</code>	High support threshold (default: 0.7)
<code>sup_lo</code>	Low support threshold (default: 0.6)
<code>backend</code>	Backend for Stan compilation: "auto" (default), "rstan", or "cmdstanr". If "auto", the function uses 'rstan' when available, otherwise tries 'cmdstanr'.

Details

This function implements a Bayesian GLM with AR(1) errors for assessing causal relationships between economic variables. It uses Leave-Future-Out cross-validation with sliding windows to evaluate temporal stability of relationships. The function no longer requires 'cmdstanr' at install time; if 'backend = "cmdstanr"' is requested but 'cmdstanr' (and a working CmdStan) are not available, it gracefully falls back to 'rstan'. In any case, heavy computations are not run in package examples or tests.

Value

A list containing:

bench_bayes	Full results for all pairs
winners_070	Pairs with support ≥ 0.70
winners_060	Pairs with support ≥ 0.60
rank_out	Output from ranking function

Examples

```
## Not run:
# Example usage
result <- bglmar1(
  data_path = file.path(tempdir(), "data.xlsx"),
  circ_vars = c("TC_SPOT_CAN_US", "TC_SPOT_US_CAN", "TC_SPOT_US_REMB",
               "IPC", "TdI_LdelT", "TasaDescuento"),
  prod_vars = c("ValorExportaciones", "Real_Net_Profit",
               "RealSocialConsumptionPerWorker2017", "RealWage_PPP2017",
               "CapitalStock_PPP2017", "LaborProductivity_PPP2017",
               "InvestmentPerWorker_PPP2017"),
  backend = "auto"
)

## End(Not run)
```

bsts_model

Bayesian Structural Time Series Model

Description

Implements Bayesian Structural Time Series models with Leave-Future-Out validation for assessing causal relationships between economic variables with temporal stability.

Usage

```
bsts_model(
  data_path,
  circ_vars,
  prod_vars,
  max_lag = 6,
  lfo_init_frac = 0.8,
  lfo_h = 6,
  lfo_step = 6,
  niter = 2000,
  burn = 500,
  seed = 123,
```

```

    seasonality = NULL,
    support_min = 0.6,
    folds_min = 5,
    sup_hi = 0.7,
    sup_lo = 0.6,
    out_dir = NULL
)

```

Arguments

<code>data_path</code>	Path to Excel file containing the data
<code>circ_vars</code>	Character vector of circulation variable names
<code>prod_vars</code>	Character vector of production variable names
<code>max_lag</code>	Maximum number of lags for independent variables (default: 6)
<code>lfo_init_frac</code>	Initial fraction for LFO (default: 0.8)
<code>lfo_h</code>	Horizon for LFO (default: 6)
<code>lfo_step</code>	Step size for LFO (default: 6)
<code>niter</code>	Number of MCMC iterations (default: 2000)
<code>burn</code>	Number of burn-in iterations (default: 500)
<code>seed</code>	Random seed (default: 123)
<code>seasonality</code>	Seasonality parameter (NULL for none, 12 for monthly)
<code>support_min</code>	Minimum support threshold (default: 0.6)
<code>folds_min</code>	Minimum number of folds required (default: 5)
<code>sup_hi</code>	High support threshold (default: 0.7)
<code>sup_lo</code>	Low support threshold (default: 0.6)
<code>out_dir</code>	Output directory for results (default: "output_bsts")

Details

This function implements Bayesian Structural Time Series models for assessing causal relationships between economic variables. It uses Leave-Future-Out cross-validation with tuning between Local Level and Local Linear Trend specifications. The methodology is described in detail in the methodological document "DETALLES METODOLOGICOS SPACESTATE MODEL.docx".

Value

A list containing:

<code>rank_ss_all</code>	Full results for all pairs
<code>winners_ss_070</code>	Pairs with support ≥ 0.70
<code>winners_ss_060</code>	Pairs with support ≥ 0.60
<code>summaries_ss</code>	Summary statistics

Examples

```
## Not run:
# Example usage
result <- bsts_model(
  data_path = file.path(tempdir(), "data.xlsx"),
  circ_vars = c("TC_SPOT_CAN_US", "TC_SPOT_US_CAN", "TC_SPOT_US_REMB",
               "IPC", "TdI_LdelT", "TasaDescuento"),
  prod_vars = c("ValorExportaciones", "Real_Net_Profit",
               "RealSocialConsumptionPerWorker2017", "RealWage_PPP2017",
               "CapitalStock_PPP2017", "LaborProductivity_PPP2017",
               "InvestmentPerWorker_PPP2017")
)

## End(Not run)
```

ecm_mars

Error Correction Model with Multivariate Adaptive Regression Splines

Description

Implements a robust ECM benchmark with MARS enhancement for analyzing cointegration relationships between economic variables with temporal stability validation.

Usage

```
ecm_mars(
  data_path,
  circ_vars,
  prod_vars,
  cointeg_rule = "either",
  eg_p_cutoff = 0.05,
  ecm_p_cutoff = 0.05,
  lag_max_ecm = 4,
  min_tr = 20,
  min_te = 8,
  rolling_cv_enable = TRUE,
  rolling_cv_window = "sliding",
  rolling_cv_initial_frac = 0.8,
  rolling_cv_initial_min = 40,
  rolling_cv_test = 12,
  rolling_cv_step = 12,
  nested_tune = TRUE,
  nested_initial_f = 0.6,
  nested_test = 6,
  nested_step = 3,
  mars_grid = expand.grid(degree = c(1, 2), nk = c(15, 25, 35, 50, 65)),
```

```

    support_min = 0.75,
    folds_min_abs = 5,
    parallel_enable = TRUE,
    parallel_workers = max(1, parallel::detectCores() - 1)
)

```

Arguments

<code>data_path</code>	Path to Excel file containing the data
<code>circ_vars</code>	Character vector of circulation variable names
<code>prod_vars</code>	Character vector of production variable names
<code>cointeg_rule</code>	Cointegration rule ("either" for EG or Johansen, "both" for both)
<code>eg_p_cutoff</code>	Significance level for EG/Phillips-Ouliaris test (default: 0.05)
<code>ecm_p_cutoff</code>	Significance level for $\lambda < 0$ test in linear ECM (default: 0.05)
<code>lag_max_ecm</code>	Maximum lags in ΔY and ΔX for linear ECM (default: 4)
<code>min_tr</code>	Minimum training rows for MARS (default: 20)
<code>min_te</code>	Minimum test rows (default: 8)
<code>rolling_cv_enable</code>	Whether to enable rolling CV (default: TRUE)
<code>rolling_cv_window</code>	Type of window for rolling CV ("sliding" or "expanding", default: "sliding")
<code>rolling_cv_initial_frac</code>	Initial fraction for rolling CV (default: 0.8)
<code>rolling_cv_initial_min</code>	Minimum initial observations (default: 40)
<code>rolling_cv_test</code>	Test horizon for rolling CV (default: 12)
<code>rolling_cv_step</code>	Step size for rolling CV (default: 12)
<code>nested_tune</code>	Whether to enable nested tuning (default: TRUE)
<code>nested_initial_f</code>	Initial fraction for nested tuning (default: 0.6)
<code>nested_test</code>	Test horizon for nested tuning (default: 6)
<code>nested_step</code>	Step size for nested tuning (default: 3)
<code>mars_grid</code>	Data frame with MARS tuning parameters
<code>support_min</code>	Minimum proportion of valid folds (default: 0.75)
<code>folds_min_abs</code>	Minimum absolute number of valid folds (default: 5)
<code>parallel_enable</code>	Whether to enable parallel processing (default: TRUE)
<code>parallel_workers</code>	Number of parallel workers (default: <code>detectCores() - 1</code>)

Details

This function implements an Error Correction Model enhanced with Multivariate Adaptive Regression Splines for analyzing cointegration relationships between economic variables. It includes comprehensive temporal validation through rolling-origin cross-validation and nested tuning for MARS parameters. The methodology is described in detail in the methodological document "DETALLES METODOLOGICOS DE ECM-MARS2.docx".

Value

A data frame with evaluation results for all pairs

Examples

```
## Not run:
# Example usage
result <- ecm_mars(
  data_path = file.path(tempdir(), "data.xlsx"),
  circ_vars = c("ER.SPOT.CAN.US", "ER.SPOT.US.CAN", "ER.SPOT.US.REMB",
               "CPI", "TreasuryBonds10y", "FedDiscountRate"),
  prod_vars = c("Exports", "RealNetProfit", "RealSocialConsumptionPerWorker2017",
               "RealWagePPP2017", "CapitalStockPPP2017",
               "LaborProductivityPPP2017", "InvestmentPerWorkerPPP2017")
)

## End(Not run)
```

Index

`bglmar1`, 2
`bsts_model`, 4
`ecm_mars`, 6